

HIGHWAY ROADMARKING ADHESION PROMOTER

Description

A fast drying solvent based adhesion promoter, containing a special blend of solvents and additives to give adhesion to difficult substances.

Available: 20 litre

Typical Uses

- Tenacious binding of drop-on beads, particularly Silane coated beads.
- As a general high durability roadmarking paint with glass beads.

Properties

Resin System	Nil
Pigmentation	Nil
Finish	Clear
Colour	Nil
Dilution Rate	Nil
Theoretical Coverage	10 – 15 m ² per litre
Dry Time @ 25°C	< 10 minutes
Number of Coats	1
Clean Up	Toluene P F 4

Performance / Limitations

- Can be used on painted surfaces to aid adhesion.
- Can be used on concrete/weathered or polished surfaces anywhere adhesion is required.
- Not recommended for damp or wet surfaces.
- Coverage dependent on surface type/condition and weather/application conditions.
- Available in 20 litre pails and 600ml Aerosol.

Preparation

- Surfaces must be clean, dry and free from grease, oil, etc.
- Can be directly applied to bare, unprimed or unsealed surfaces.

Application

- Mix thoroughly before use.
- For Aerosol, hold can in an upside down position (approximately 2 to 10 cm from substrate), applying pressure to the plastic lever within the cap. Distance from substrate will determine the width of applied adhesion promoter.
- Can be applied by brush, roller or spray.

Health and Safety

- For detailed information refer to the Material Safety Data Sheet and label for this product.
- Provide adequate ventilation during use.
- Avoid breathing vapour. A vapour cartridge respirator is recommended.
- If eyes become contaminated flush thoroughly with water.
- Wearing of safety glasses is highly recommended.
- Product is **FLAMMABLE**.