

HIGHWAY CHLORINATED RUBBER SUPER B

Description

A blend of modified alkyd and chlorinated rubber resin based paint with a higher level of durability than alkyd roadmarking paints. Particularly suitable for use on carpark and warehouses including or concrete.

Applied by spray.

Available: 20 Litre

Typical Uses

- For application to road surfaces with a relatively high vehicle traffic count.
- For road marking where good glass bead holding is required.
- As a carpark paint over both concrete and bituminous substances.

Properties

Resin System	Acrylic Emulsion
Pigmentation	Titanium Dioxide, Hard wearing extenders
Finish	Matt
Colour	White
Dilution Rate	Use as supplied. Can be thinned up to 5 % with Thinners PF 4 (fast dry).
Volume Solids	54% ± 2.0%
Theoretical Coverage	2.5 – 3.0 m ² /litre @ 220 - 180 µm DFT
Dry Time @ 25°C	<7 minutes rapid dry
Number of Coats	1
Clean Up	Toluene

- Application to concrete is problematic due to large variations in drying agents and surface finishes available, plus surface contaminations.
- Improved retention of glass beads (when compared to alkyd based paints).
- Dry times will be longer in cold or high humid, windless weather.
- NOT recommended for use over damp or wet surfaces.
- NOT recommended for use under 10°C. Below this temperature product will not form a film and adhere to substrate.

Preparation

- Surfaces must be clean, dry, free from oil, grease, lichen, etc. and any loose, flaky material.
- Can be applied to bare, unprimed or unsealed bitumen based surfaces*

*For concrete painting see concrete preparation information sheet

Application

- Stir thoroughly before use.
- Recommended application method is by spraying, either airless or conventional.
- May be thinned up to 5% with Thinners PF 4 (fast dry) to aid application.
- For first coat application to new or aged hot mix on car parks or tennis courts etc, apply a dust coat of approximately 50 Microns DFT, leave to dry for 24 hours minimum then apply second coat to desired film build.

Performance / Limitations

- Excellent resistance to bleeding.
- Excellent adhesion to aged road marking paint.

HIGHWAY CHLORINATED RUBBER SUPER B

Health and Safety

- For detailed information refer to the Material Safety Data Sheet and label for this product.
- Provide adequate ventilation during use.
- When spraying wear a quality mask as inhalation of mist may cause respiratory irritation.
- Wear eye protection when handling as splashes to the eye may cause irritation.
- Product is **FLAMMABLE**.
- Do not Smoke in work area
- Handle with care

NEW ZEALAND: Eastgate Business Park, 800 Te Ngae Road, Rotorua
PO BOX 7084, Te Ngae, Rotorua 3042, New Zealand
P: 0800 33 44 75 | F: 0800 33 44 76 | E: orders@damarindustries.co.nz
www.damarindustries.co.nz

AUSTRALIA: 25 Hargraves Place, Wetherill Park, NSW, 2164
PO BOX 6599, Wetherill Park 2164, Australia
P: +61 2 9756 4511 | F: +61 2 9756 4511
www.damarindustries.com.au

DISCLAIMER: This information is not a specification and is given in good faith. Since conditions of use are beyond the manufacturers control, all information given is without warranty, implied or otherwise, and is not intended to be exhaustive. Final determination for suitability of the product for the use contemplated is the sole responsibility of the user. It is also the user's responsibility to ensure that this information is current prior to using the product.